
WIRING INSTRUCTIONS



SWITCH SO INSULATION IS FLUSH-SUBFLUSH WITH OPENING

Wire No.	Wire Color	Origin or Part No.	Gauge	Length	PECIFICATIONS Terminals, Connectors and End Wire Preparation
1	White	Pin Hsg. Assy.	20		Component of pin housing assembly.
2	White	Pin Hsg. Assy.	20		Component of pin housing assembly.
3	Green	Pin Hsg. Assy.	20		Component of pin housing assembly / Strip 3/16" for T1.
4	Blue	23-94-6245	20	2-1/8"	Strip 3/16" for T4 / Strip 5/16" and tin.
5	Blue	23-94-6230	20	4-1/8"	Strip 3/16" for T3 / Strip 5/16" and tin.
6	White	23-94-6235	20	4-1/8"	Strip 3/16" for T4 / Strip 5/16" and tin.
7		Switch			Supplied with switch.
8	Black	Module	18	1-5/8"	Strip 3/16" for T4.
9	Black	Module	18	5-3/8"	Strip 5/16" and tin.
10	Black	Module	18	5-3/8"	Strip 3/16" for T2.
11	White	23-94-6240	20	3-3/8"	Strip 3/16" for T3 / Strip 3/16" for T4.

NOTE: All leads must be held to ± 1/8". All lead lengths are before stripping.

TERMINAL DESCRIPTION						
Code	Part No.	Onty.				
T1	23-74-0615	1				
T2	23-74-0900	1				
ТЗ	23-74-1090	2				
T4	23-74-1100	4				
CONNECTOR DESCRIPTION						