

WIRING INSTRUCTIONS


TITLE

D-HANDLE TOOLS

MILWAUKEE ELECTRIC TOOL CORP. 13135 WEST LISBON RD. BROOKFIELD, WIS.

DATE
Sept. '97

BULLETIN
58-01-0288



WIRING SPECIFICATIONS

Wire No.	Wire Color	Origin or Part No.	Gauge	Length	Terminals, Connectors and End Wire Preparation
1	White	Cord	18	3-3/4"	Strip 3/8" and tin.
2	Black	Cord	18	3-3/4"	Strip 3/8" and tin.
▲ 3	Green	Cord	18	4-1/2"	Strip 3/16" and tin for C1.
4	Black	Switch Assy.	18	5-7/8"	Strip 3/8" and tin.
5	White	23-94-6175	18	8"	Strip 3/16" for T3 / Strip 3/8" tin.
▲ 6	Green	23-94-6100	16	8-3/4"	Strip 3/16" for T1 / Strip 3/16 and tin for C1.
7	Yellow	23-94-6110	18	5-5/16"	Strip both ends 3/16" for T3.
8	Black	Switch Assy.	18	5-1/4"	Strip 1/4" for T4.
9	Black	Switch Assy.	18	7-1/4"	Strip 1/4" for T4.
10	Red	Switch Assy.	18	5-1/4"	Strip 3/16" for T3.
11	Black	Switch Assy.	18	9-7/16"	Strip 5/16" and tin.
12	Black	Switch Assy.	18	10-3/32"	Strip 3/16" for T2.

BULK LEAD WIRE - BULLETIN 58-01-0003

▲ FOR DOUBLE INSULATED, DISREGARD WIRES AND TERMINALS

NOTE:

All leads must be held to $\pm 1/8"$.
All lead lengths are before stripping.

TERMINAL DESCRIPTION

Code	Part No.	Qty.
▲ T1	23-74-0605	1
T2	23-74-0900	1
T3	23-74-1060	4
T4	23-74-0410	2

CONNECTOR DESCRIPTION

▲ C1	22-56-0456	1
------	------------	---

Drwg. 1