

# Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200.

This standard must be consulted for specific requirements.

#### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Dry Cut Diamond Abrasives **Drawing Number:** 58-97-1170

Issue Date: March 2015
Supersedes Date: July 2011

**Milwaukee Electric Tool Corporation** 

13135 West Lisbon Road Brookfield, Wisconsin 53005

www.milwaukeetool.com

Company Phone Number: 262-781-3600 or

1-800-729-3878

**Emergency Contact Number:** 1-800-424-9300

Chemtrec: United States only

Recommended use of product surface conditioning is abrasive material for mechanical industry

# **SECTION 2: HAZARDS IDENTIFICATION**

#### **GHS Classification**

Health	Environmental	Physical
Eye Irritation: No classified hazards	Acute Toxicity: No classified hazards	Flammable liquid: No classified hazards
Skin Irritation: No classified hazards	Chronic Toxicity: No classified hazards	
Acute Toxicity, Oral: No classified hazards		
Acute Toxicity, Inhalation: No classified		
hazards		

# **GHS Label**

No applicable labeling

Hazard Statements	Precautionary Statements
May cause eye irritation	IF IN EYES: rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do.
	IF eye irritation persists: get medical attention/advice.
May cause mild skin irritation	Wash skin/hands thoroughly after handling.
	IF skin irritation occurs: get medical attention/advice.
May be harmful if swallowed	IF SWALLOWED: call a POISON CENTER or doctor/physician if you
	feel unwell.
May be harmful if inhaled	IF INHALED: call a POISON CENTER or doctor/physician if you feel
	unwell.
	Use personal protective equipment as required.

Some dust generated from intended use may cause some irritation to eyes, skin and respiratory. Fiberglass content is a possible carcinogen when dust is inhaled.

## **Classified Hazards**

This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200. This SDS contains valuable information for the safe handling and proper use of this product. Save this SDS for future reference.

## **Other Hazards**

None known

# **SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

Components listed in this section may contribute to the potential hazards associated with the dust that has been generated from the base material being ground, cut or sanded.

Chemical Name	CAS#	Concentration
Cobalt	7440-84-4	100
Copper	7440-50-8	91
Chromium	7440-47-3	3
Manganese	7439-96-5	<1
Molybdenum	7439-98-7	
Nickel	7440-02-0	53
Silicon	7440-21-3	
Tin	7440-31-5	
Tungsten	7440-33-7	0 – 0.24
Diamond	7782-40-3	76 - 100
Tungsten Carbide	12070-12-1	0-0.3
Titanium	7440-32-6	0-0.2
Titanium Carbide	12070-08-5	0-0.1

Note: This product has been evaluated and does not require any hazard warning label under the OSHA Hazard Communication Standard.

Note: This abrasive product may be comprised of one or the other of the above abrasives as well as two or more of the substances.

## **SECTION 4: FIRST AID MEASURES**

#### **EYE CONTACT:**

Dust generated by grinding, sanding and cutting may cause eye irritation. Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. If symptoms persist, contact a physician.

## **SKIN CONTACT:**

Remove product from the skin by washing with a mild soap and water. If irritation persists seek medical attention.

## **INHALATION:**

Excessive dust inhalation may affect breathing function. Use recommended OSHA or NIOSH approved respirator as required. If inhaled remove to fresh air. Seek medical help if symptoms persist.

## **INGESTION:**

Ingestion is not anticipated. Seek medical help if symptoms persist.

# **CARCONGENICITY:**

Fiberglass content is a possible carcinogen when dust is inhaled.

## **MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:**

No further data known.

## **SECTION 5: FIRE FIGHTING MEASURES**

## **NFPA 704 Hazard Class**

No data

# **HMIS**



- 0 (Minimal)
- 1 (Slight)
- 2 (Moderate)
- 3 (Serious)
- 4 (Severe)

#### **EXTINGUISHING MEDIA:**

Use an extinguishing agent suitable for the surrounding fire.

#### **UNUSUAL FIRE & EXPLOSION HAZARDS:**

No further data known.

# FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Emergency responders in the danger area should wear bunker gear and self-contained breathing apparatus for fires beyond the incipient stage. See Section 8 of the MSDS for other PPE to be worn as conditions warrant.

See Section 9 for Flammable Properties including Flash Point and Flammable (explosive) limits.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## Clean-Up Measures:

Use normal clean up procedures. Dispose of waste in accordance with local, state and Federal regulations.

## **SECTION 7: HANDLING AND STORAGE**

#### **HANDLING:**

Normal handling and storage methods should be used with caution not to drop or crush. Cotton fiber abrasive products should be stored in a dry area in rooms not subject to extreme temperature changes, since excessive humidity and dampness may affect some bonds. Never expose cotton fiber products to water or solvents.

Do not operate above maximum operating speed marked on the wheel.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Selection of personal protective equipment should be based upon the anticipated exposure and made in accordance with OSHA's Personal Protective Equipment Standard found in 29 CFR 1910 Subpart I. The following information may be used to assist in PPE selection.

Chemical Name	OSHA PEL	ACGIH TLV	California Prop 65 Reg. Y/N	IARC/NTP Y/N
Cobalt	.05mg/m³	.05mg/m³		N
Copper	1mg/m³	1mg/m³		N
Chromium	.5mg/m³	.5mg/m³		N

Manganese	5mg/m³	5mg/m³	N	
Molybdenum	10mg/m³	10mg/m³	N	
Nickel	5mg/m³	5mg/m³	N	
Silicon	10mg/m³ (Dust)	10mg/m³	N	
		(Dust)		
Tin	2mg/m³	2mg/m³	N	
Tungsten	5mg/m³	5mg/m³	N	
Diamond	15mg/m³	10mg/m³	N	
Tungsten Carbide	5mg/m³	5mg/m³	N	
Titanium	15mg/m³	10mg/m³	N	
Titanium Carbide	15mg/m³	ND	N	

#### **EYE PROTECTION**

Wear eye protection appropriate to prevent eye exposure. Most of the dust that is generated is from the material being ground, sanded or cut and may cause eye irritation. Wearing goggles or full face shield is recommended.

#### **SKIN PROTECTION:**

Protective gloves may be useful.

#### **RESPIRATORY PROTECTION:**

A respirator may be worn to reduce the exposure to dust. Select a NIOSH/MSHA approved respirator appropriate for the type and physical character of the airborne material. A self-contained breathing apparatus is recommended in all situations where airborne contaminant concentration has not been confirmed to be below safe levels. Respirator use should comply with the OSHA Respirator Protection Standard found in CFR 1910.134.

#### **ENGINEERING CONTROLS:**

Normal general ventilation is expected to be adequate. It is recommended that ventilation be designed in all instances to maintain airborne concentrations at lowest practicable levels. Ventilation should at a minimum, prevent airborne concentrations from exceeding any exposure limits listed in Section 2 of this MSDS.

The user may wish to refer to 29 CFR 1910.1000 (d) (2) and the ACGIH "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices" (Appendix C) for the determination of exposure limits of mixtures. An industrial hygienist or similar professional may be consulted to confirm that the calculated exposure limits apply.

#### **OTHER PRECAUTIONS:**

Use of this product may create elevated sound levels. Hearing protection should be worn where required.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Data represent typical values and are not intended to be specifications. NA=Not Applicable; ND=Not Determined

Physical state:	Powder	Flammability (solid, gas):	NΑ
Colour:	Various	Upper Explosive Limits (vol % in air):	NΑ
Odor:	Odorless	Lower Explosive Limits (vol % in air):	NΑ
Odor Threshold:	NA	Vapor pressure:	NΑ
pH:	NA	Vapor density:	NΑ
Melting/Freezing Point:	NA	Relative density:	NΑ
VOC Content:	NA	Solubility:	NΑ
Boiling Point:	NA	Partition Coefficient:	NΑ
Flash Point:	NA	Auto-ignition Temperature:	NΑ

Evaporation Rate:	. NA	Decomposition Temperature:ND
Specific Gravity:	. NA	Viscosity:ND

#### **SECTION 10: STABILITY AND REACTIVITY**

#### **INCOMPATIBLE MATERIALS:**

This product is incompatible with strong acids.

## **DECOMPOSITION PRODUCTS MAY INCLUDE:**

Dust from the product being ground, sanded or cut.

## **CONDITIONS TO AVOID:**

Avoid contact with incompatible materials and exposure to extreme temperatures. Airborne fine powder dust in confined spaces.

#### **POLYMERIZATION:**

This product is not expected to polymerize.

#### **CHEMICAL STABILITY:**

This product is stable.

## **REACTIVITY:**

Stable under normal ambient and anticipated conditions of use.

# **SECTION 11: TOXICOLOGY INFORMATION**

LIKELY ROUTES OF EXPOSURE: Inhalation, Eye and Skin contact

#### **ACUTE SYMPTOMS AND EFFECTS:**

Inhalation:No further toxicological data knownEye contact:No further toxicological data knownSkin contact:No further toxicological data knownIngestion:No further toxicological data known

## OTHER:

No further data known.

# **SECTION 12: ECOLOGICAL INFORMATION**

#### **ECOTOXICOLOGICAL INFORMATION:**

This product has not been evaluated for ecotoxicity. As with any industrial chemical, exposure to the environment should be prevented and minimized wherever possible.

#### **TOXICITY:**

No data available

## PERSISTENCE AND DEGRADABILITY (BIOPERSISTENCY & BIODEGRADABILITY):

The degree of biodegradability and persistence of this product has not been determined.

#### POTENTIAL OF BIOACCUMULATION:

No data available

#### **MOBILITY IN SOIL:**

No data available

#### OTHER ADVERSE EFFECTS:

No data available

## **SECTION 13: DISPOSAL CONSIDERATIONS**

#### WASTE DISPOSAL:

Dispose in accordance with the local, state and Federal regulations.

## **SECTION 14: TRANSPORT INFORMATION**

#### **DOT HAZARDOUS MATERIAL INFORMATION:**

Not otherwise DOT regulated.

## **SECTION 15: REGULATORY INFORMATION**

#### **FEDERAL REGULATIONS:**

## **SARA 313:**

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### Clean Water Act / Oil Pollution Act:

This product contains mineral oil and is subject to regulation by Section 311 of the Clean Water Act and the Oil Pollution Act. Releases of the product into or leading to surface waters must be reported to the National Response Center at 1-800-424-8802.

## **CERCLA Reportable Quantity:**

Any components listed below have been assigned a reportable quantity (RQ) by the Federal EPA. Releases of the product into the environment that exceed the RQ for a particular component must be reported to the National Response Center at 1-800-424-8802.

# **Toxic Substance Control Act:**

The components of this product are listed on the TSCA Inventory.

# **Ozone Depleting Substances:**

This product contains no ozone depleting substances as defined by the Clean Air Act.

#### **Hazardous Air Pollutants:**

Any components listed below are defined by the Federal EPA as hazardous air pollutants.

#### **STATE REGULATIONS:**

This product contains mineral oil, and as used, may be regulated by the state used oil regulations. Check with the appropriate state agency to determine whether such a regulation exists.

No further data known.

# **SECTION 16: OTHER INFORMATION**

## **ABBREVIATIONS:**

TSCA	Toxic Substance Control Act
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous
OSHA	Occupational Safety and Health
IARC/NTP	International Agency for Research on Cancer/National Toxicology Program
SARA	Superfund Amendments and Reauthorization Act of 1986
ACGIH	American Conference of Governmental Industrial Hygienists
NIOSH/MSHA	National Institute for Occupational Safety Health/
	Mine Safety and Health Administration
WHMIS	Workplace Hazardous Materials Information System

Prepared by: Milwaukee Electric Tool Corporation

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. *MILWAUKEE ELECTRIC TOOL CORPORATION* makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained from the use thereto. All risks associated with product use are assumed by the user.