



TO INFORM YOU

PRODUCT SUPPORT BULLETIN # 353

TO: AUTHORIZED *Portable Electric Tool* SERVICE STATIONS
factory SERVICE CENTERS
SALES COMPANIES

DATE: DECEMBER, 2000

FROM: Corbert A. Garb - National Service Manager

TOOL(S) \ PRODUCT(S) AFFECTED

6365, 6369, 6375-20, 6376-20, 6405-6, 6410, 6411, 6460, 6465, 6465-68, 6466, 6480, 6490, 6494, 6494-04, 6496 Circular Saw / Miter Saw

SUBJECT: 49-08-5270 6oz Tube TYPE "Y" GREASE
49-08-5275 1lb Can TYPE "Y" GREASE

List Price \$ 8.95 USD

List Price \$17.95 USD

TYPE "Y" GREASE [49-08-5270 **6oz Tube** / 49-08-5275 **1lb Can**] is the new Grease Standard / Lubrication for current production of 6365, 6369, 6375-20, 6376-20, 6405-6, 6410, 6411, 6460, 6465, 6465-68, 6466, 6480, 6490, 6494, 6494-04, 6496 Circular Saws/ Miter Saws.

The grease consistency / viscosity of **TYPE "Y" GREASE** is a #1 weight. It is a high-speed gear lubricant that contains extreme pressure additives to minimize metal to metal contact in the high-speed gearing of circular saw. A non-bleeding [smooth amber color] lithium base will eliminate oil leakage from around the seal area of the saw's gear case.

Grease Consistency Rating
NLGI * Consistency

Number	Appearance
0	very soft
1	soft
2	medium
3	medium hard
4	hard
5	very hard
6	block type

* National Lubricating Grease Institute

Milwaukee Grease

Type

Consistency
Rating

A	2
B	3-1/2
D	2
E	2
F	1-1/2 & 2
G	1
J	2
K	1-1/2
L	2
N	1-1/2
O	0
P	2
Q	semi-fluid
R	0
U	3
Y	1

Note! **TYPE "Y" GREASE** will out perform however, is not compatible with the **TYPE "O"** [pink] & **TYPE "R"** [purple] **GREASE** previously used in 63XX series Saws. **TYPE "Y" GREASE** can be substituted for both TYPE "O" & TYPE "R" GREASE though, it requires complete removal of ALL TYPE "O" or TYPE "R" GREASE from the gearing and gear case.

This bulletin is for informational purposes. PLEASE NOTE ON SERVICE PARTS LIST; Domestic 54-40-0172, 54-40-0182, 54-40-0251, 54-40-0261, 54-40-0401, 54-40-1111, 54-40-1128, 54-40-1160, 54-40-5100, 54-40-5401, 54-40-5426, 54-40-6492, 54-40-6551, 54-40-6576 International 55-40-0181, 55-40-6550